

# Metallotion Protec CE 15 L at 5 & 20 ltr



## Referenced by Brands below













### Characteristics

- METALLOTION PROTEC CE15L is a ready-to-use water based anti-spatter liquid against welding spatters which is sprayed on workpieces and moulds
- · CE15L is efficient when wet and dry
- · CE15L is a temporary corrosion protection
- Bio-welding & degreasing-lotion, ready-to-use, water based no silicones

# Advantageous

- Minimization of costs and saving of time as no post treatment is
- Higher quality by welds without pores and perfect metal surfaces
- Consumption savings of about 30 % compared with competitive products by improved spreading capacity
- · Adhesion promoter for each type of surface technology
- METALLOTION PROTEC CE15L is tested and approved for welding, painting, electro-coating, powder-coating, galvanisation, zinccoating
- Optimization of welding process
- · CE15L is approved for automotive industry, vehicle industry, offshore technology, container engineering, steel construction, crane industry, etc
- · CE15L does not form pores during welding
- CE15L protects each metal surface and removes grease and oil at the same time, afterwards simple cleaning is sufficient
- CE15L is very economic and does not form residues

Specifications	
Type of active substance	Vegetable fatty acid components with water emulsifiable
Density ( 20°C )	0.98 g/ml
Viscosity (40°C)	2.1 mm <sup>2</sup> /s
Flash - point	na
Pour Point	-3° C
pH - value	7.1

substance	vegetable fatty acid components with water emulsifiable		
Density ( 20°C )	0.98 g/ml		
Viscosity (40°C)	2.1 mm <sup>2</sup> /s		
Flash - point	na		
Pour Point	-3° C		
pH - value	7.1		

Item Code	Item Name	MoQ
315.01.001.1	Metallotion Protec CE 15 L at 5 ltr	1 Pail
315.01.002.1	Metallotion Protec CE 15 L at 20 ltr	1 Pail



www.bumi.info D 7