















Main Applications

- Shipyards
- · Steel Structure
- · Chemical and process industry

I DOSTRIL

SAW - Tractor 1000

Advantageous

- Digitizing tractor can be achieve various wires welding such as filament, flux cored wire, and it can save 10 sets of welding data, which saves time. Both the wire feeding and the tractor moving speed are stable, which provides an excellent welding
- Digital display control, design and convenient operation.
- Accurate arc start.

- Dual drive wire feeder with straightening configuration to provide stablewire feeding, good centralizing, excellent traction, and strong wire feeding force. Greatly improved welding performances.
- Suitable for Kobewel CC/CV Inverter S 1000 i
- · Strong, rigid and stiff especially where you need it most

Specifications		
Input voltage	DC 110 V (supplied by Power Source)	
Welding current	1.000 A	
Wire diameter	2 - 6 mm	
Wire type	Copper - Coated Solid Wire	
Wire speed	0.3 ~ 3 m/min	
Feeding mode	Automatic	
Welding speed	0.2 ~ 1.5 m/min	
Adjustable torch height	70 mm	
Adjustable tractor head height	100 mm	
Adjustable longitudinal distance of tractor head around cross beam	± 30 mm	
Rotate-able angle of tractor head around cross beam	≥ ± 90°	
Adjustable longitudinal distance of tractor head	100 mm	
Torch inclination	45°	
Tractor head inclination	± 45°	
Wire spool capacity	25 Kg	
Flux container volume	6 Liter	
Weight	54 Kg	

tem Code	Item Name	MoQ
101.18.002	SAW Machine - Tractor 1000	1 Unit
	 Power Cable for SAW 70 mm2 at 15 m Control Cable at 15 m Feedroll diameter 3.2, 4 & 5 mm Contact Tip diameter 3.2, 4 & 5 mm Wrench 14 / 17 mm Socket Wrench 14 mm Hex. Key 8 mm Rail Track at 1 m 	



Bumi PT. Bumi Teknik Utama

Item Code	Item Name	MoQ
Optional Accesso	ories for SAW	
201.40.001	SAW Tractor - Feed Roll - Steel Ø 2.0 mm	1 Pcs
201.40.002	SAW Tractor - Feed Roll - Steel Ø 2.4 mm	1 Pcs
201.40.003	SAW Tractor - Feed Roll - Steel Ø 3.2 mm	1 Pcs
201.40.004	SAW Tractor - Feed Roll - Steel Ø 4.0 mm	1 Pcs
201.40.005	SAW Tractor - Feed Roll - Steel Ø 5.0 mm	1 Pcs
201.41.001	SAW Tractor - Contact Tip - M12 Ø 2.0 mm	1 Pcs
201.41.002	SAW Tractor - Contact Tip - M12 Ø 2.4 mm	1 Pcs
201.41.003	SAW Tractor - Contact Tip - M12 Ø 3.2 mm	1 Pcs
201.41.004	SAW Tractor - Contact Tip - M12 Ø 4.0 mm	1 Pcs
201.41.005	SAW Tractor - Contact Tip - M12 Ø 5.0 mm	1 Pcs





C 22 www.bumi.info