Bumi PT. Bumi Teknik Utama







Bolted Joint

Cu + Al Multi – Conductor Cable, Solid and Multi - Stranded

Insulated According to IEC 60900, Usable up to 1000 V AC / 1500 V DC VDE Tested, also in Conformance to GPSG

(Equipment and Product Safety Act)

With Opening Spring

Advantageous

- For cutting copper and aluminum single conductors as well as multiple stranded cables
- · Not suitable for steel wire and wire ropes
- Precision ground, hardened blades
- · Clean and smooth cut without crushing and deformation
- One-hand operation using ratchet principle

Black Lacquered - Multi Component Grips



Item Code

233.22.001

233.22.002

233.22.003

Black Lacquered - Insulated - Multi Component Grips VDE Tested





233.22.002 : Large cutting capacity :

maximum 52 mm dia. / 380 mm2

Item Name

-	4	В	5
	0	0	
1			
4			

Cable Cutter Ratchet Action - 250 mm - Black Lacquered - Multi Component Grips

Cable Cutter Ratchet Action - 280 mm - Black Lacquered - Multi Component Grips

Cable Cutter Ratchet Action - 250 mm - Black Lacquered Insulated - Multi Comp. Grips - VDE Tested

Ratchet principle and two stage ratchet drive for easier cutting



 $233.22.001\ \&\ 233.22.002$: Fixed handle with support area as an aid to position the cutters on a flat surface

Cable Cutter Ratchet Action



- · Two-stage ratchet drive for easy cutting
- Simple handling as a result of low weight and compact design can be used even in confined areas
- Guard prevents operators' fingers being pinched
- High-grade special tool steel, forged, oil hardened
- · Little hand force required due to very high transmission ratio

Specifications			
Length	mm	250	280
Cutting Cable Ø	mm	32	52
Cutting Cable Section Ø	mm2	240	380
MCM		500	750
Weight	gram	676	860

Specifications					
Length	mm	250			
Cutting Cable Ø	mm	32			
Cutting Cable Section Ø	mm2	240			
MCM		500			
Weight	gram	652			

