



## Cable Shears with Twin Cutting Edge



**Bolted Joint**



**Cu + Al Multi – Conductor Cable,  
Solid and Multi - Stranded**

### Advantageous

- For cutting copper and aluminum cables
- Not suitable for steel wire and hard drawn copper conductors
- Precision ground, hardened blades
- By dividing the cutting actions into initial cut ( insulating sheath in the front cutting area ) and final cut ( conductor in the back cutting area ) , cables up to Ø 20 mm can be cut in one hand operation
- Less effort required due to favorable lever ratio and optimized cutting edge geometry
- Guard prevents operators' fingers being pinched
- Adjustable bolted joint, self retaining screw
- High grade special tool steel, forged, oil hardened
- Clean and smooth cut without crushing and deformation

### Burnished - Multi Component Grips



**PATENTED**



### Specifications

Length	mm	<b>200</b>
Cutting Cable Ø	mm	20
Cutting Cable Section Ø	mm <sup>2</sup>	70
AWG		2/0
Weight	gram	324

Item Code	Item Name
233.21.001	Cable Shears with Twin Cutting Edge - 200 mm - Burnished - Multi Component Grips



#### Initial Cut :

Using the front cutting edge to cut the insulating sheath on larger cable diameters leaves an ergonomic handle opening width



#### Final Cut :

After cutting the sheath in the front profile the cut is finished through the metal part of the cable in the rear profile. Initial cut in the front profile, final cut in the rear profile - to keep it as easy as possible