



Gas Cutting Nozzle



Advantageous

- Quality gas cutting nozzle for accurate economical and safer cutting

Acetylene



Acetylene / A N M E			Pressure kg / cm ²		Consumption NI / hour			Cutting Speed mm / min
Item Code	No.	Plate thickness	Oxygen	Acetylene	Cutting Oxygen	Pre-heat Oxygen	Acetylene	
201.25.001	00	- 5	1.5	0.2	690	410	370	- 650
201.25.002	0	5 - 10	2.0	0.2	1.200	410	370	660 - 550
201.25.003	1	10 - 15	2.5	0.2	2.100	480	430	550 - 490
201.25.004	2	15 - 30	3.0	0.2	3.400	480	430	490 - 400
201.25.005	3	30 - 40	3.0	0.2	4.300	480	430	400 - 350
201.25.006	4	40 - 50	5.0	0.2	5.600	750	680	425 - 350
201.25.007	5	50 - 100	5.0	0.25	8.800	860	780	350 - 250

LPG



LPG / P N M E			Pressure kg / cm ²		Consumption NI / hour			Cutting Speed mm / min
Item Code	No.	Plate thickness	Oxygen	LPG	Cutting Oxygen	Pre-heat Oxygen	LPG	
201.25.008	00	- 5	1.5	0.2	690	1.180	310	- 650
201.25.009	0	5 - 10	2.0	0.2	1.200	1.180	310	660 - 550
201.25.010	1	10 - 15	2.5	0.2	2.100	1.180	310	550 - 490
201.25.011	2	15 - 30	3.0	0.25	3.400	1.370	360	490 - 400
201.25.012	3	30 - 40	3.0	0.25	4.300	1.370	360	400 - 350
201.25.013	4	40 - 50	3.5	0.3	6.500	1860	490	350 - 320
201.25.014	5	50 - 100	4.0	0.3	11.000	1860	490	320 - 200