

## Impact Driver 1/4" - C18 ID



**Keyless 1/4" Hex Chuck**  
Quick and easy bit changes

**LED Light**  
Illuminates work area

**Variable Speed Trigger**  
Complete user control

**Forward / Lock / Reverse Switch**  
Well positioned, easy operation

**Belt Hook**  
Easy Portability

**Battery Fuel Gauge**  
Display remaining run-time & decrease frustration

**Red Lithium-Ion Battery**  
High runtime, increase durability and performance, rubber protected



### Advantageous

- Ultimate driving power and performance to tackle the hardest jobs
- 4-Pole Motor delivers maximum power, tool efficiency and run-time
- Powerful 158 Nm torque, high performance
- Impact mechanism increases driving speed to 2.200 RPM
- Delivers 3.200 Impacts per minute, increased productivity
- Lightweight and compact, excellent handling and minimizes user fatigue
- Rubber over-mold front, rear and top grips, secure grip and work surface protection

### Specifications

No load speed	0 - 2.200 RPM
Torque	158 Nm
Percussion rate	0 - 3.200 IPM
Tool reception	1/4" ( 6.35 mm ) Hex - Keyless
LED light	Yes
Battery voltage	18 Volts
Battery type	M18 BX 3.0 Ah Red Lithium-Ion
Charge time	30 minutes
Dimension ( L x W x H )	160 x 70 x 250 mm
Weight with battery pack	1.6 Kg

Milwaukee's 4-pole frameless motor is more powerful, more compact, more efficient and far more durable than a traditional canned motor.



Milwaukee frameless motor : far smaller, yet far more powerful

Conventional cordless motor

Item Code	Item Name	MoQ
134.10.001.1	<b>Impact Driver 1/4 inch, C18 ID Package</b> <ul style="list-style-type: none"> <li>• Carrying case</li> <li>• Charger C1418</li> <li>• Belt hook for impact driver 1/4 inch, C18 ID</li> </ul>	<b>1 Set</b>
<b>Standard Accessories</b>		
134.10.001	Impact Driver 1/4 inch, C18 ID	1 Unit
234.22.005	Battery 18 V, 3.0 Ah, M18 BX	2 Pcs
<b>Optional Accessories</b>		
234.22.005	Battery 18 V, 3.0 Ah, M18 BX	1 Pc
234.26.001	Shockwave "Phillips" Screwdriving Bits - PH 1 - 25 mm	2 Pcs
234.26.002	Shockwave "Phillips" Screwdriving Bits - PH 1 - 25 mm	2 Pcs
234.26.003	Shockwave "Phillips" Screwdriving Bits - PH 1 - 25 mm	2 Pcs
234.26.004	Shockwave "Torx" Screwdriving Bits - TX 15 - 25 mm	2 Pcs
234.26.005	Shockwave "Torx" Screwdriving Bits - TX 20 - 25 mm	2 Pcs
234.26.006	Shockwave "Torx" Screwdriving Bits - TX 25 - 25 mm	2 Pcs
234.26.007	Shockwave "Torx" Screwdriving Bits - TX 30 - 25 mm	2 Pcs
234.26.008	Shockwave "Slotted" Screwdriving Bits - SL 0.6 x 4.5 - 25 mm	2 Pcs
234.26.009	Shockwave "Slotted" Screwdriving Bits - SL 0.8 x 4.5 - 25 mm	2 Pcs
234.26.010	Shockwave "Slotted" Screwdriving Bits - SL 1.2 x 4.5 - 25 mm	2 Pcs
234.26.011	Shockwave Magnetic Bit Holder - 1/4" Hex - 60 mm	1 Pcs
234.26.012	Shockwave Socket Adaptor - 1/4" Hex to 1/4" Square Drive - 50 mm	1 Pcs
234.26.013	Shockwave Socket Adaptor - 1/4" Hex to 1/2" Square Drive - 50 mm	1 Pcs
234.26.014	Magnetic Nut Driver 5.5 mm - M 3, 65 mm	1 Pcs
234.26.015	Magnetic Nut Driver 6.0 mm - M 3.5, 65 mm	1 Pcs
234.26.016	Magnetic Nut Driver 7.0 mm - M 4, 65 mm	1 Pcs
234.26.017	Magnetic Nut Driver 8.0 mm - M 5, 65 mm	1 Pcs
234.26.018	Magnetic Nut Driver 10 mm - M 6, 65 mm	1 Pcs
234.26.019	Magnetic Nut Driver 12 mm - M 7, 65 mm	1 Pcs
234.26.020	Magnetic Nut Driver 13 mm - M 8, 65 mm	1 Pcs
234.26.021	Magnetic Nut Driver 17 mm - M 10, 65 mm	1 Pcs