



KOBECUT - TCT Cutter depth 50 mm




Main Applications

- Steel fabricators
- Shipyard
- Power plant
- Boiler
- Bridges

Chip Breaker System

1. Pre Cutter
2. Middle Cutter
3. Post Cutter



Universal Shank suitable for

- Mag Drill with Weldon
- Mag Drill with One Touch



Advantageous

- Suitable for drilling on cast iron, cast steel, carbon steel, alloy steel, stainless steel, copper, aluminum, etc.
- Drilling 5 times faster than twist drill, reduces the overall effort and time
- High performance tothing with pre, middle and post cutter, double bevelled tips for smooth drilling and less vibration
- Cutting tips geometry for steady flow of chips and preventing chip jamming
- Minimum cross section of chip removing surface - easy cutting, low torque, low energy consumption and low friction
- Better wall design enables cutters to cut faster and more efficiently by removing less material during drilling

Item Code	Item Size	MoQ
225.02.001	Ø 14 mm	1 Pc
225.02.002	Ø 15 mm	1 Pc
225.02.003	Ø 16 mm	1 Pc
225.02.004	Ø 17 mm	1 Pc
225.02.005	Ø 18 mm	1 Pc
225.02.006	Ø 19 mm	1 Pc
225.02.007	Ø 20 mm	1 Pc
225.02.008	Ø 21 mm	1 Pc
225.02.009	Ø 22 mm	1 Pc
225.02.010	Ø 23 mm	1 Pc
225.02.011	Ø 24 mm	1 Pc
225.02.012	Ø 25 mm	1 Pc
225.02.013	Ø 26 mm	1 Pc
225.02.014	Ø 27 mm	1 Pc
225.02.015	Ø 28 mm	1 Pc
225.02.016	Ø 29 mm	1 Pc
225.02.017	Ø 30 mm	1 Pc
225.02.018	Ø 31 mm	1 Pc
225.02.019	Ø 32 mm	1 Pc
225.02.020	Ø 33 mm	1 Pc
225.02.021	Ø 34 mm	1 Pc
225.02.022	Ø 35 mm	1 Pc
225.02.023	Ø 36 mm	1 Pc
225.02.024	Ø 37 mm	1 Pc
225.02.025	Ø 38 mm	1 Pc
225.02.026	Ø 39 mm	1 Pc
225.02.027	Ø 40 mm	1 Pc
225.02.028	Ø 41 mm	1 Pc
225.02.029	Ø 42 mm	1 Pc

Item Code	Item Size	MoQ
225.02.030	Ø 43 mm	1 Pc
225.02.031	Ø 44 mm	1 Pc
225.02.032	Ø 45 mm	1 Pc
225.02.033	Ø 46 mm	1 Pc
225.02.034	Ø 47 mm	1 Pc
225.02.035	Ø 48 mm	1 Pc
225.02.036	Ø 49 mm	1 Pc
225.02.037	Ø 50 mm	1 Pc

Item Code	Item Name	MoQ
-----------	-----------	-----

Optional Accessories



225.05.003	Pin TCT 50 Ø 14 - 17 mm, 6.34 x 106 mm	1 Pc
209.09.004	Pin TCT 50 Ø 12 - 50 & TCT 50 Ø 14 - 17 mm, 6.35 x 102 mm	1 Pc
225.05.004	Pin TCT 50 Ø 18 - 50 mm, 7.98 x 108 mm	1 Pc
209.09.003	Pin TCT 50 Ø 18 - 50 & AL 50 Ø 51 - 100 mm, 8 x 102 mm	



225.06.001	Tool Holder - MT2 - 19.05 x 50, with Internal Cooling	1 Pc
225.06.002	Tool Holder AMT3 with Internal Cooling	1 Pc
209.12.005	Tool Holder AMT2 with Internal Cooling	1 Pc
209.12.006	Tool Holder AMT3 with Internal Cooling	1 Pc
208.25.010	Coolant Tank	1 Pcs
308.02.001	Coolant 2000 at 1 Liter	1 Pc
308.02.002	Coolant 2000 at 5 Liter	1 Pc