
Bumi PT. Bumi Teknik Utama



Main Applications

- · Shipyards
- Steel Structure
- Chemical and process industry

Advantageous

- Welding quality is much better than the traditional thyristor submerged arc welding equipments.
- CC/CV arc characteristics combined with two adaptive feeding modes (Stick and SAW), delivers excellent welding performance, meeting the different requirements of various SAW processes.
- Automatic compensation for mains fluctuations with ± 15%.
- Capable of operating with up to 50m long welding cable.

Power Source CC/CV Inverter S 1000i



S 1000 i - CC/CV

- Highly efficient soft switching IGBT technology. IGBT and MCU technology.
- PWM control technology provides optimal constant output current and superior dynamic characteristics, and assures the consistency of the weld penetration and width even for a long welding bead.
- Digital display control cabinet is the combination of striking design and convenient operation.

Specifications		Item Code
Rated output current	1.000 A	101.18.001
Rated output	100 A / 24 V ~ 1.000 A / 44 V	
Duty cycle	100 %	Optional A
Max. open circuit voltage	93 V	101.18.002
Welding current adjustment	Stepless	208.03.002
Suitable for	SAW Gouging SMAW = MMA	Optional A 201.27.003
Input phase	3 Phase	201.27.003
Input power	380 V at ± 15 %	Optional A
Frequency	50 / 60 Hz	208.03.005
Rated input current	85 A	208.03.006
Rated input	52.7 KVA	208.03.007
Power factor	0.90	208.03.008
Fower lactor		208.03.001
Index protection	IP 21	208.03.002
Weight	115 Kg	208.03.003
Dimension (LxWxH)	900 x 460 x 810 mm	



Item Code	Item Name	MoQ	
101.18.001	Power Source CC/CV Inverter - S 1000 i	1 Set	
	Ground Cable at 5 m, 2 set		
Optional Accessories for SAW			
101.18.002	SAW - Tractor 1000	1 Unit	
208 03 002	Plug to Electrode Holder 600 A, 70 mm2 at 10 m	1 Set	
200.00.002		1 000	
Optional Accessories for Gouging			
201.27.003	Gouging Torch G4 - 1000 A - 2.1 m / 7 feet	1 Set	
Optional Accessories for SMAW / MMA			
208.03.005	Plug to Electrode Holder 400 A, 50 mm2 at 5 m	1 Set	
208.03.006	Plug to Electrode Holder 400 A, 50 mm2 at 10 m	1 Set	
208.03.007	Plug to Electrode Holder 400 A, 50 mm2 at 20 m	1 Set	
208.03.008	Plug to Electrode Holder 400 A, 50 mm2 at 25 m	1 Set	
208.03.001	Plug to Electrode Holder 400 A, 70 mm2 at 5 m	1 Set	
208.03.002	Plug to Electrode Holder 400 A, 70 mm2 at 10 m	1 Set	
208.03.003	Plug to Electrode Holder 400 A, 70 mm2 at 20 m	1 Set	
208.04.007	Plug to Ground Clamp 600 A, 50 mm2 at 5 m	1 Set	
208.04.008	Plug to Ground Clamp 600 A, 50 mm2 at 10 m	1 Set	
208.04.004	Plug to Ground Clamp 600 A, 70 mm2 at 5 m	1 Set	
208.04.005	Plug to Ground Clamp 600 A, 70 mm2 at 10 m	1 Set	
208.04.006	Plug to Ground Clamp 600 A, 70 mm2 at 15 m	1 Set	

General Accessories

201.22.009	Welding Helmet - Solarmatic Blue	1 Set
201.22.010	Welding Helmet - Solarmatic Red	1 Set
201.22.011	Welding Helmet - Solarmatic Green	1 Set

www.bumi.info

