

Rotabest 130



Oil Bath



With lifting hook for easy mobility



Advantageous

- Oil Bath gearbox, reduces wear on the gearbox significantly, even under extreme conditions
- Mechanical slipping clutch, protects the gearbox from overload and comes into action automatically
- Membrane keyboard, perfect ergonomics with large keys. The entire keyboard is located in a protected area (even if the machine drops)
- Soft touch grips, perfect "grip" on the handles, even with oily gloves
- Cord length 5 m, extension cord and cable drums is not required
- Metal rings, perfect protection for the magnets against penetration by metallic objects (chips, milling dust, etc)

Capacity

Core drill Ø	12 - 130 mm
Core drill cutting depth	50 mm with tool holder MT-3 75 mm with tool holder MT-4
Twist drill Ø	Up to Ø 45 mm with MT-4
Tap	M 42

Specifications

Input power	2.500 Watt
Speed with load	Gear 1 : 30 - 80 RPM Gear 2 : 50 - 120 RPM Gear 3 : 130 - 350 RPM Gear 4 : 210 - 550 RPM
Stroke	230 mm
Adjustable motor in height	100 mm
Tool adaptor	MT-4
Cooling	Internal via tool holder
Voltage	230 V - 50/60 Hz
Tool Force (10 mm)	5.000 N out of 32.000 N
Magnet foot size	32.000 N
Magnet foot type	90 x 400 mm
Dimension (L x W x H)	540 x 250 x 740 mm
Weight	34.5 Kg

Suitable Cutters	Depth	Diameter
TCT - Alfra & Kobecut	35 mm	14 - 35 mm
TCT - Alfra & Kobecut	50 mm	14 - 50 mm
HSS Cobalt - Alfra & Kobecut	30 mm	12 - 40 mm
HSS Cobalt - Alfra & Kobecut	50 mm	12 - 60 mm
Alfra TCT AL	50 mm	51 - 100 mm

Item Code	Item Name	MoQ
109.01.014	Rotabest 130	1 Set
	<ul style="list-style-type: none"> • Transport case, Safety belt, Coolant unit, Chip hooky 	

Optional Accessories

209.12.005	Tool Holder AMT2 with Internal Cooling	1 Pc
225.06.001	Tool Holder - MT2 - 19.05 x 50, with Internal Cooling	1 Pc
209.12.006	Tool Holder AMT3 with Internal Cooling	1 Pc
225.06.002	Tool Holder - MT3 - 19.05 x 50, with Internal Cooling	1 Pc
225.06.003	Tool Holder - MT4 - 19.05 x 75, with Internal Cooling	1 Pc
209.12.003	Quick Drill Chuck + Weldon Shank - Ø 1 - 13 mm	1 Pc
225.06.011.1	Quick Chuck - Universal Shank - Ø 1 - 13 mm - 1 Pc	1 Pack
209.12.001	HSS Countersink and Deburrer with Weldon Shank Ø 25 mm	1 Pc
209.12.002	HSS Countersink and Deburrer with Weldon Shank Ø 40 mm	1 Pc
209.12.007	Tool Holder AL-3	1 Pc
209.12.008	Tool Holder AL-4	1 Pc
209.12.027	Drill Chuck + Weldon Shank for Twist Drills Ø 1 - 13 mm	1 Pc
209.12.004	Reducing Sleeve MT3 to MT2	1 Pc
209.12.029	Reducing Sleeve MT4 to MT2	1 Pc
209.12.012	Quick Drill Chuck + Morse Taper No.3 Shank for Twist Drill Ø 1 - 16 mm	1 Pc
209.12.023	Drill Chuck + Morse Taper No.2 Shank for Twist Drill Ø 1 - 16 mm	1 Pc
209.12.028	Drill Chuck + Morse Taper No.3 Shank for Twist Drill Ø 1 - 16 mm	1 Pc
209.12.010	Bio 2000	1 Pc
308.02.001	Coolant 2000 at 1 Liter	1 Pc
308.02.002	Coolant 2000 at 5 Liter	1 Pc