



Rotabest TCT Cutter depth 50 mm




Main Applications

- Steel fabricators
- Shipyard
- Power plant
- Boiler


Chip Breaker System

1. Pre Cutter
2. Middle Cutter
3. Post Cutter



Universal Shank suitable for

- Mag Drill with Weldon
- Mag Drill with One Touch



Advantageous

- Drilling 5 times faster than twist drill
- For heavy to light jobs
- High performance toothing with pre, middle and post cutter, double bevelled
- CAD-optimized cutting geometry for steady flow of chips, uniquely shaped chip grooves to prevent chip jamming,
- Optimum regular chip breaking - smooth and excellent cutting capacity, good chip production at each tooth, regular chip flow
- Rapid drill core removal by ejector pin
- Instant centering, no running off center with good concentricity also suitable for NC and CNC Machine
- Minimum cross section of chip removing surface - easy cutting, low torque, low energy consumption
- High tool hardness due to optimum raw material and special heat treatment made it long life and suitable for difficult materials
- High tenacity of cutter, specially graduated hardness - lower risk of tool break especially under rough working conditions
- Industrial scale manufacturing by state of the art CNC technology, results optimum function, best reproducibility and constant quality

Item Code	Item Size	MoQ
209.02.001	Ø 14 mm	1 Pc
209.02.002	Ø 15 mm	1 Pc
209.02.003	Ø 16 mm	1 Pc
209.02.004	Ø 17 mm	1 Pc
209.02.005	Ø 18 mm	1 Pc
209.02.006	Ø 19 mm	1 Pc
209.02.007	Ø 20 mm	1 Pc
209.02.008	Ø 21 mm	1 Pc
209.02.009	Ø 22 mm	1 Pc
209.02.010	Ø 23 mm	1 Pc
209.02.011	Ø 24 mm	1 Pc
209.02.012	Ø 25 mm	1 Pc
209.02.013	Ø 26 mm	1 Pc
209.02.014	Ø 27 mm	1 Pc
209.02.015	Ø 28 mm	1 Pc
209.02.016	Ø 29 mm	1 Pc
209.02.017	Ø 30 mm	1 Pc
209.02.018	Ø 31 mm	1 Pc
209.02.019	Ø 32 mm	1 Pc
209.02.020	Ø 33 mm	1 Pc
209.02.021	Ø 34 mm	1 Pc
209.02.022	Ø 35 mm	1 Pc
209.02.023	Ø 36 mm	1 Pc
209.02.024	Ø 37 mm	1 Pc
209.02.025	Ø 38 mm	1 Pc
209.02.026	Ø 39 mm	1 Pc
209.02.027	Ø 40 mm	1 Pc
209.02.028	Ø 41 mm	1 Pc
209.02.029	Ø 42 mm	1 Pc
209.02.030	Ø 43 mm	1 Pc
209.02.031	Ø 44 mm	1 Pc
209.02.032	Ø 45 mm	1 Pc
209.02.033	Ø 46 mm	1 Pc
209.02.034	Ø 47 mm	1 Pc
209.02.035	Ø 48 mm	1 Pc
209.02.036	Ø 49 mm	1 Pc
209.02.037	Ø 50 mm	1 Pc

Item Code	Item Name	MoQ
-----------	-----------	-----

Optional Accessories



209.09.003	Pin TCT 50 Ø 18 - 50 mm & AL 50 Ø 51 - 100 mm, 8 x 102 mm	1 Pc
209.09.004	Pin TCT 50 Ø 14 - 17 mm & HSS 50 Ø 12 - 50 mm, 6.35 x 102 mm	1 Pc
225.05.003	Pin TCT 50 Ø 14 - 17 mm, 6.34 x 106 mm	1 Pc
225.05.004	Pin TCT 50 Ø 18 - 50 mm, 7.98 x 108 mm	1 Pc



209.12.005	Tool Holder AMT 2 with Internal Cooling	1 Pc
209.12.006	Tool Holder AMT 3 with Internal Cooling	1 Pc
225.06.001	Tool Holder - MT2 - 19.05 x 50, with Internal Cooling	1 Pc
225.06.002	Tool Holder AMT3 with Internal Cooling	1 Pc



208.25.010	Coolant Tank	1 Pcs
------------	--------------	-------



308.02.001	Coolant 2000 at 1 Liter	1 Pcs
308.02.002	Coolant 2000 at 5 Liter	1 Pcs