



## Rotabest V32



### Advantageous

- Horizontal metal core drilling machine for the tightest conditions. Perfect for use where regular metal core drilling machines cannot go due to their height
- Application areas : Steel construction ( in between girder flanges ), vehicle construction ( truck frames ), bridge construction, tower construction, tunnel construction, everywhere where it's narrow
- Magnet foot components from the Rotabest series. The total height is just 227 mm and can even be reduced to 185 mm by removing the handle
- The spur gear unit is designed for robust use and is fed using a ratchet. Reversible for right and left handed operation
- Equipped with 2 sided pillar guidance
- Another advantage : the design of the angled gear unit ensures permanent lubrication and prevents dry running
- Used with the proven motors and magnet foot components from the Rotabest series
- Cord length 5 m, extension cord and cable drums is not required
- Metal rings, perfect protection for the magnets against penetration by metallic objects ( chips, milling dust, etc )
- Performance and weight optimization, dimensioning and coil sizing are ideally matched

Capacity	
Core drill Ø	12 - 32 mm
Core drill cutting depth	30 mm
Countersinking Ø	10 - 32 mm

Specifications	
Input power	900 watt
Speed under load	450 RPM
Tool adaptor	19 mm Weldon shank
Cooling	Integrated, Automatically
Voltage	230 V - 50/60 Hz
Tool Force ( 10 mm )	2.100 N out of 16.000 N
Magnet adhesion	16.000 N
Magnet foot size	95 x 200 mm
Magnet foot type	Rigid
Power cord	5.0 m
Dimension ( L x W x H )	360 x 127 x 227 mm
Weight	12.5 Kg

Suitable Cutters	Depth	Diameter
TCT - Alfra & Kobecut	35 mm	14 - 35 mm
HSS Cobalt - Alfra & Kobecut	30 mm	12 - 35 mm

Item Code	Item Name	MoQ
<b>109.01.011</b>	<b>Rotabest V32</b>	<b>1 Set</b>
	<ul style="list-style-type: none"> <li>• Transport case, Coolant pressure flask, Allen key for Weldon shank, Safety belt, HSS yellow depth 25 mm - Ø18 mm, Pilot pin 6.35 x 70 mm, for HSS 25</li> </ul>	

### Optional Accessories

209.12.003	Quick Drill Chuck + Weldon Shank -	1 Pc
225.06.011.1	Quick Chuck - Universal Shank - Ø 1	1 Pack
209.12.027	Drill Chuck + Weldon Shank for Twist	1 Pc
209.12.001	HSS Countersink and Deburrer with	1 Pc
209.12.002	HSS Countersink and Deburrer with	1 Pc
209.12.010	Bio 2000	1 Pc
308.02.001	Coolant 2000 at 1 Liter	1 Pc
308.02.002	Coolant 2000 at 5 Liter	1 Pc

